



MARINE

Lubricant Range



NMMA approved lubricants - complete marine protection and performance.

At Rock Oil, we utilise our extensive expertise in 2-stroke and 4-stroke lubricants to produce an exceptional range of marine lubricants suitable for both inboard and outboard applications. Among this diverse array of top-tier lubricants, we are particularly proud to have achieved the esteemed NMMA certification for our leading marine lubricants, MP3 Ultra and MP+ Sport, reflecting the exceptional standards we consistently uphold across our product range.

We proudly offer a broad spectrum of marine lubricants formulated to meet specific performance and application needs. Every product in our range reflects our commitment to quality and performance, ensuring a suitable solution for every customer's requirements.

OUTBOARD MARINE ENGINE OIL

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
MP3 ULTRA	2-stroke, advanced synthetic, DFI	NMMA TC-W3® (NO. RL 92402B) 
MP PLUS SPORT 10W-40	4-stroke, synthetic, SAE 10W-40	API SM • NMMA FC-W CC (NO. FC13799W), NMMA FC-W 
MP PLUS SPORT 5W-30	4-stroke, advanced synthetic, SAE 5W-30	NMMA FC-W(CC)®
MP3 SPORT	2-stroke, semi-synthetic, DFI / non-DFI	NMMA TC-W3®
BIO MARINE 3	2-stroke, ester-based, biodegradable, non-toxic	NMMA TC-W3® 

INBOARD MARINE ENGINE OIL

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
MP4 SPORT	4-stroke, synthetic, SAE 15W-40	API CK-4, CJ-4, CI-4 • ACEA E7, E11 • CATERPILLAR ECF-3, ECF-2 & ECF-1A • CUMMINS 20086 • DETROIT DIESEL 93K222 • DEUTZ DQC-III-18-LA, DQC-III-10-LA • MACK EO-S 4.5 • MAN M3775, M3575 • MERCEDES-BENZ / DAIMLER TRUCK 228.31 (DTFR 15C100) • MTU TYPE 2.1 • RENAULT RVI RLD-4, RLD-3 • VOLVO VDS-4.5 • FORD WSS M2C171 F1
MP LITE-D	4-stroke multi-grade diesel, SAE 15W-40	API SF/CC
MPR INJECTOR	2-stroke, advanced synthetic, non TC-W3® injector/pre-mix	JASO FD & FC • ISO L-EGD • API TC • ROTAX 253 • HUSQVARNA 346 & 372 MPR INJECTOR MEETS THE REQUIREMENTS OF SEA-DOO JET SKIS AND OTHER ROTAX ENGINEED MARINE EQUIPMENT.



HEAVY-DUTY MARINE ENGINE OIL

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
MARINE-GUARD 3015 TP	Medium alkalinity for medium & high-speed trunk piston diesel engines	API CF • SAE 30 • TBN 15
MARINE-GUARD 4015 TP	Medium alkalinity for medium & high-speed trunk piston diesel engines	API CF • SAE 40 • TBN 15

ANCILLARY MARINE PRODUCTS

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
MARINE PSF	Power steering & transmission fluid	GM DEXRON II
MARINE HSF	Hydraulic steering fluid	DIN 51524 PART 2
MP GEAR OIL	Extreme-pressure gear oil (Blue/Green), SAE 80W-90	API GL-5
SUPER MARINE INHIBITOR	LIGHT MINERAL OIL BLENDED WITH SOPHISTICATED CORROSION INHIBITORS AND OXIDATION STABILISERS	

SPECIALIST MARINE GREASE

PRODUCT NAME	DESCRIPTION	SPECIFICATIONS, APPROVALS, AND RECOMMENDATIONS
MPG UNIVERSAL MARINE GREASE	Premium quality anhydrous calcium grease	NLGI-3 • WHITE • ANHYDROUS CALCIUM • -20°C TO +120°C
MG STERN TUBE GREASE	Premium quality water resistant calcium grease	WHITE • CALCIUM • -20°C TO +110°C
WATER RESISTANT 2 GREASE	Aluminium complex grease	NLGI-2 • BROWN • ALUMINUM COMPLEX • -20°C TO +140°
HD ADHESIVE GREASE	Semi-synthetic water resistant grease	GREEN • 1000 BASE OIL • -7°C TO +140
PRO-GUARD CA 2Z GREASE	Premium quality water resistant calcium grease	WHITE • CALCIUM • -20°C TO +110°C



ANTI-FREEZE / COOLANTS

KOOL-GUARD MARINE MPG	Mono Propylene Glycol (MPG), Marine	ASTM D3306 TYPE II • BS 6580 (2010) • AFNOR NF R15-601 (EXCEPT FOR RESERVE ALKALINITY)
KOOL-GUARD MEG -38	Mono Ethylene Glycol (MEG), Blue	DILUTION 50:50 AFNOR NF R15-601 • AS 2108 • ASTM D3306 • BS 6580 (2010) • BTC CLASSIFICATION TYPE 2E • CUNA NC 956-16 • FVV HEFT R443 • ONORM V 5123 • SAE J1034 • UNE 26-361
KOOL-GUARD XL -38	Mono Ethylene Glycol (MEG), OAT	DILUTION 50:50 ASTM D3306 • ASTM D4985 • BS 6580 (2010) • DAF 74002 • SAE J1034 • FFV HEFT R443 • CUNA NC 956-16 • UNE 26361-88 • JIS K2234 • NATO S759 • AFNOR NF R15-601 (EXCEPT FOR RESERVE ALKALINITY) • CHRYSLER MS 9176 • CUMMINS CES 14603 • FORD ESE M97B49-A, WSS-M97B44-D & ESD M97B49-A • GM 1899M, US 6277M, OPEL GM QL130100 • JOHN DEERE H24 B1 & C1 • LEYLAND TRUCKS LTS 22 AF 10 • MACK 014GS 17004 • MAN 248, 324 (SNF), & B&W D 36 5600 • MERCEDES/DAIMLER TRUCK MB 325.3 (DTFR 29C110) • RENAULT 41-01-001-D • VAG TL 774D/F (G12/G12+) • VOLVO VCS (EXCEPT COLOUR)
KOOL-GUARD VCS 50:50 PREMIX	Mono Ethylene Glycol (MEG), OAT	DILUTION 50:50 ASTM D3306 • ASTM D4985 • BS 6580 (2010) • SAE J1034 • FFV HEFT R443 • CUNA NC 956-16 • UNE 26361-88 • JIS K2234 • NATO S759 • AFNOR NF R15-601 (EXCEPT FOR RESERVE ALKALINITY) • CHRYSLER MS 9176 • CUMMINS CES 14603 • FORD ESE M97B49-A, WSS-M97B44-D & ESD M97B49-A • GM 1899M, US 6277M, OPEL GM QL130100 • JOHN DEERE H24 B1 & C1 • LEYLAND TRUCKS LTS 22 AF 10 • MACK 014GS 17004 • MAN 248, 324 (SNF), & B&W D 36 5600 • MERCEDES/DAIMLER TRUCK MB 325.3 (DTFR 29C110) • RENAULT 41-01-001-D • VAG TL 774D/F (G12/G12+) • VOLVO VCS
KOOL-GUARD PSi-OAT -38	Mono Ethylene Glycol (MEG), Silicated OAT	DILUTION 50:50 AS 2108-2004 • ASTM D 3306, D 4985, D 6210, D7583 • PN-C 4007:2000 • SAE J1034 • ÖNORM V 5123 • CUNA NC 956-16 • JIS K 2234:2206 • CHINA GB 29743-2013 • SANS 1251:2005 • BS 6580:2010 • VOLVO VCS-2 • DEUTZ, DQC CC-14 • DEUTZ-FAHR >04/2017 • HUERLIMANN >04/2017 • LAMBORGHINI-TRACTORS >04/2017 • MAN DIESEL & TURBO >04/2017 • SAME >04/2017 • VOLVO CARS TR-31854114-002 • JOHN DEERE >2011 • PERKINS

Depending on the range, Rock Oil products are available in multiple sizes, including 400ml aerosols and 1L / 4L / 5L / 20L / 210L / bulk containers.

All products and information are correct at the time of publication. The company reserves the right to change formulations and specifications without prior notice.
For more detailed information on any product and confirmation of the latest specifications please contact us. Full product data sheets and health and safety information is available on request.

Contact sales@rockoil.co.uk for order information and expert advice.

✉ Malone House, 90 Priestley Street, Warrington, Cheshire, WA5 1ST

☎ +44 (0) 1925 636191



rockoil.co.uk